



Touring Compact Line Array Loudspeaker

## CLA-108F / CLA-115S



### CLA-108F

Line Array Loudspeaker

#### KEY FEATURES

- Precision and high efficiency touring line array
- Max. SPL: 123dB (single)
- Frequency bandwidth: 60Hz~18KHz ±3dB (single)
- 90° (-6dB), MF or HF with horn loaded control
- 1x10" low driver with sensitivity: 101dB (1w/1m) (single)
- 1x8" mid driver with, sensitivity: 103dB (1w/1m) (single)
- 2x1" high compression driver with sensitivity: 106dB (1w/1m) (single)
- Quick and integrated hang parts, adjustable vertical splay angle from 0° to 7°
- Stack with CLA-115S as integrated Line array system
- Can ground stack or fly with line array system

#### APPLICATIONS

- Installation : mosque, church, conference, bistro, musicale, theater conference, etc
- Touring mobile : multifunctional hall, concert, theme park, dance club

SPECIFICATIONS	
Frequency Response	65Hz~18KHz (± 3dB)
Level Bestow Angle	90° (-6dB) 120° (-12dB)
Vertical Bestow Angle	7.5° (-6dB)
Low Frequency	1x10" / 3" voice coil
Middle Frequency	1x8" / 2" voice coil
High Frequency	2x1" / compression drivers
Rating Power	LF: 200W(rms) MF +HF 100W(rms)
Peak Power	LF: 800W MF:400W HF:220W
Impedance	8 Ω
Crossover	800Hz, 5000Hz (active or passive)
Dimensions	780x310x440(mm)
Packing Dimensions	490x360x840mm
Weight	45kg



### CLA-115S

Line Array Loudspeaker

#### KEY FEATURES

CLA-115S is the newest subwoofer with high SPL output in a compact horn loaded, can hang up as array system or ground stack. With ultra wide low frequency response and high SPL output, using a 15" (390mm) low frequency driver with 4" (100mm) voice coil, its latest technology combines high efficiency hyperbolic dispersion with low frequency extension driver loaded into enclosure.

SPECIFICATIONS	
Frequency Response	45Hz-118Hz
LF	1 x 15" (4" voice coil)
Sensitivity	105dB
Rated Power	400W(rms)
Peak Power	1200W
Impedance	8 ohm
Dimension	745x650x540mm
Packing Dimensions	815x580x695mm
Weight	55kg