



Professional Karaoke Speaker 3-way

KSP-85 / KSP-105 / KSP-125 / KSP-285

Features

- 3-way Karaoke speakers
- Auto protection circuitry system improved the safety factor
- A/two high efficiency 8"/10" woofer with MF and HF driver sound of power and purity
- Baked, black-paint covering and molded steel grill
- Standard mounting holes



KSP-85



KSP-105



KSP-125



KSP-285

SPECIFICATIONS	KSP-85	KSP-105	KSP-125	KSP-285
Frequency Response	48Hz-18KHz(±3dB)	45Hz-20KHz(±3dB)	43Hz-20KHz(±3dB)	43Hz-20KHz(±3dB)
Components	Low 8"x1(50mm) Mid 5"x1(25mm) Hi 3"x1(20mm)	Low 10"x1(64mm) Mid 5"x1(25mm) Hi 3"x1(20mm)	Low 12"x1(64mm) Mid 5"x1(25mm) Hi 3"x1(20mm)	Low 8"x2(50mm) Mid 5"x1(25mm) Hi 3"x1(20mm)
Impedance	4 ohm	4 ohm	4 ohm	4 ohm
Continuous Power Handling	100W	200W	250W	2500W
Peak Power	200W/5Min	400 W/5min	500 W/5min	500 W/5min
Sensitivity	93 dB (1w/1m)	97 dB (1w/1m)	98 dB (1w/1m)	100 dB (1w/1m)
Dimensions	270x440x270 mm	300x500x320 mm	350x530x300 mm	330x5500x320 mm
Weight	12kg	15kg	16kg	19kg

Professional Karaoke Speaker 2-way

KTV-803 / KTV-103

Features

- 2-way Karaoke speakers
- Over-load protection circuitry
- A high efficiency 8"/10" woofer with dual 3" HF
- Black-paint covering and molded steel grill
- Standard mounting holes



KTV-803



KTV-103

SPECIFICATIONS	KTV-803	KTV-103
Frequency Response	48Hz-20KHz(±3dB)	45Hz-20KHz(±3dB)
Components	Low 8" x1 Hi 3" x 2	Low 10" x1 Hi 3" x 2
Nominal Impedance	8 Ω	8 Ω
Continuous Power Handling	150W	200W
Peak Power	300W	400W
Sensitivity	93dB	96dB
Dimensions	450x260x290 mm	500x280x300 mm
Weight	11kg	12kg